

500 Series: Multi-Size Plugs with Seal Rib



Example: 500-812

- Made with DuPont Kevlar®
- Safety Pressure Relief Valve
- 1 Piece Forged Zinc Plated Eyelets
- Field Replaceable Inflation Fitting
- Positive Seal Rib
- Manufactured From Extra Thick, All Natural, Soft, Durable Rubber
- Pole Attachment Available

Pipe Plugs & Accessories

500 Series: Multi-Size Plugs with Seal Rib								
PART #	SIZE RANGE	DIAMETER	LENGTH	WEIGHT	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE BACK PRESSURE		
						PIPE SIZE	AIR	WATER
500-48	3.8"-8.0" 100 mm-200 mm	3.5" 89 mm	20.0" 508 mm	3.5 lbs 1.6 kg	40 psi 2.8 bar	4.0"	15 psi	40 ft
						100 mm	1.0 bar	12.2 m
						6.0"	15 psi	35 ft
						150 mm	1.0 bar	10.7 m
500-610	5.0"-10.0" 125 mm-250 mm	4.9" 124 mm	21.0" 533 mm	6.0 lbs 2.7 kg	35 psi 2.4 bar	8.0"	10 psi	30 ft
						200 mm	0.69 bar	9.1 m
						6.0"	15 psi	40 ft
						150 mm	1.0 bar	12.2 m
						8.0"	15 psi	35 ft
500-812	7.5"-12.0" 200 mm-300 mm	7.0" 178 mm	22.0" 559 mm	10.0 lbs 4.5 kg	35 psi 2.4 bar	200 mm	1.0 bar	12.2 m
						10.0"	15 psi	35 ft
						250 mm	1.0 bar	10.7 m
						12.0"	10 psi	35 ft
						300 mm	0.7 bar	10.7 m
500-1016	9.5"-16.0" 250 mm-400 mm	9.0" 229 mm	23.0" 584 mm	15.0 lbs 6.8 kg	35 psi 2.4 bar	10.0"	15 psi	40 ft
						250 mm	1.0 bar	12.2 m
						12.0"	15 psi	35 ft
						300 mm	1.0 bar	10.7 m
						14.0"	10 psi	35 ft
						350 mm	0.69 bar	10.7 m
500-1218	11.5"-18.0" 300 mm-450 mm	11.0" 279 mm	25.0" 635 mm	19.0 lbs 8.6 kg	35 psi 2.4 bar	16.0"	10 psi	30 ft
						400 mm	0.69 bar	9.1 m
						12.0"	15 psi	40 ft
						300 mm	1.0 bar	12.2 m
						15.0"	15 psi	35 ft
500-1521	14.0"-21.0" 350 mm-550 mm	13.3" 338 mm	28.0" 711 mm	26.0 lbs 11.8 kg	35 psi 2.4 bar	375 mm	1.0 bar	12.2 m
						18.0"	15 psi	35 ft
						450 mm	1.0 bar	10.7 m
						21.0"	10 psi	35 ft
						525 mm	0.7 bar	10.7 m



600/650 Series: Multi-Size Back Plugs / Leak Locators

- DuPont Kevlar® Reinforced
- Ozone Protected Rubber Surface
- Sturdy Steel Internal End Plates with Inflation & Test-Thru Ports
- Wrapped Finish Surface
- Extra 1/4" Thickness - No Oversleeve Necessary
- Factory Repairable - No Patches - Vulcanized
- Higher Inflation Pressure for Increased Safety Margin
- Protected with Pressure Relief Valve to Help Prevent Over Inflation

Pipe Plugs & Accessories



Example: 600-610



Example: 650-610

Available for
Rent or Sale!



Example: 600-1824



Example: 650-1824

600/650 Series: Multi-Size Back Plugs / Leak Locators

Pipe Plugs & Accessories

600/650 Series: Multi-Size Back Plugs / Leak Locators								
PART #	SIZE RANGE	DIAMETER	LENGTH	WEIGHT	REQUIRED INFLATION PRESSURE	PIPE SIZE	MAX ALLOWABLE BACK PRESSURE	
							AIR	WATER
600-46	3.8"-6.0" 100 mm-150 mm	3.5" 89 mm	13.0" 330 mm	2.5 lbs 1.1 kg	35 psi 2.4 bar	4.0" 100 mm	10 psi 0.7 bar	25 ft 7.6 m
650-46						6.0" 150 mm	10 psi 0.7 bar	25 ft 7.6 m
600-610	5.5"-10.0" 150 mm-250 mm	5.0" 127 mm	22.0" 559 mm	7.2 lbs 3.3 kg	35 psi 2.4 bar	6.0" 150 mm	15 psi 1.0 bar	40 ft 12.2 m
650-610						8.0" 200 mm	15 psi 1.0 bar	35 ft 10.7 m
						10.0" 250 mm	15 psi 1.0 bar	35 ft 10.7 m
600-812	7.5"-12.0" 200 mm-300 mm	7.0" 178 mm	22.5" 572 mm	10.0 lbs 4.5 kg	35 psi 2.4 bar	8.0" 200 mm	15 psi 1.0 bar	40 ft 12.2 m
650-812						10.0" 250 mm	15 psi 1.0 bar	35 ft 10.7 m
						12.0" 300 mm	15 psi 1.0 bar	35 ft 10.7 m
600-1016	9.0"-16.0" 225 mm-400 mm	8.8" 224 mm	25.0" 635 mm	16.0 lbs 7.3 kg	35 psi 2.4 bar	10.0" 250 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1016						12.0" 300 mm	15 psi 1.0 bar	35 ft 10.7 m
						15.0" 375 mm	15 psi 1.0 bar	35 ft 10.7 m
600-1218	11.0"-18.0" 275 mm-450 mm	10.5" 267 mm	28.0" 711 mm	21.5 lbs 9.7 kg	35 psi 2.4 bar	12.0" 300 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1218						15.0" 375 mm	15 psi 1.0 bar	35 ft 10.7 m
						18.0" 450 mm	15 psi 1.0 bar	35 ft 10.7 m
600-1224	11.0"-24.0" 275 mm-625 mm	10.5" 267 mm	47.0" 1194 mm	30.0 lbs 13.6 kg	25 psi 1.7 bar	12.0" 300 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1224						18.0" 450 mm	13 psi 0.9 bar	30 ft 9.1 m
						24.0" 600 mm	10 psi 0.7 bar	25 ft 7.6 m
600-1521	13.5"-21.0" 350 mm-550 mm	13.0" 330 mm	31.5" 800 mm	30.0 lbs 13.6 kg	35 psi 2.4 bar	15.0" 375 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1521						18.0" 450 mm	15 psi 1.0 bar	35 ft 10.7 m
						21.0" 525 mm	10 psi 0.7 bar	30 ft 9.1 m
600-1530	13.5"-30.0" 350 mm-775 mm	13.0" 330 mm	57.0" 1548 mm	55.0 lbs 24.9 kg	25 psi 1.7 bar	15.0" 375 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1530						21.0" 525 mm	13 psi 0.9 bar	30 ft 9.1 m
						30.0" 775 mm	10 psi 0.7 bar	25 ft 7.6 m
600-1824	16.0"-24.0" 400 mm-625 mm	15.5" 394 mm	35.5" 902 mm	38.5 lbs 17.5 kg	35 psi 2.4 bar	18.0" 450 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1824						21.0" 525 mm	15 psi 1.0 bar	35 ft 10.7 m
						24.0" 600 mm	10 psi 0.7 bar	30 ft 9.1 m
600-1830	16.5"-30.0" 425 mm-775 mm	16.0" 406 mm	47.0" 1194 mm	68.0 lbs 30.8 kg	25 psi 1.7 bar	18.0" 450 mm	15 psi 1.0 bar	40 ft 12.2 m
650-1830						21.0" 525 mm	15 psi 1.0 bar	35 ft 10.7 m
						24.0" 600 mm	10 psi 0.7 bar	35 ft 10.7 m
						30.0" 775 mm	10 psi 0.7 bar	30 ft 9.1 m



600/650 Series: Multi-Size Back Plugs / Leak Locators



Example: 600-2448
Deflated

Available for
Rent or Sale!



Example: 600-2448
Inflated

- DuPont Kevlar® Reinforced
- Ozone Protected Rubber Surface
- Sturdy Steel Internal End Plates with Inflation & Test-Thru Ports
- Wrapped Finish Surface
- Extra 1/4" Thickness - No Oversleeve Necessary
- Factory Repairable - No Patches - Vulcanized
- Higher Inflation Pressure for Increased Safety Margin
- Protected with Pressure Relief Valve to Help Prevent Over Inflation
- 3/4" Bypass Port

Pipe Plugs & Accessories

600/650 Series: Multi-Size Back Plugs / Leak Locators

600/650 Series: Multi-Size Back Plugs / Leak Locators								
PART #	SIZE RANGE	DIAMETER	LENGTH	WEIGHT	REQUIRED INFLATION PRESSURE	PIPE SIZE	MAX ALLOWABLE BACK PRESSURE	
							AIR	WATER
600-2036	18.5"-36.0"	18.0"	65.0"	95.0 lbs	25 psi	20.0"	15 psi	40 ft
	475 mm-950 mm	457 mm	1651 mm	43.0 kg	1.7 bar	500 mm	1.0 bar	12.2 m
650-2036						24.0"	15 psi	35 ft
						600 mm	1.0 bar	10.7 m
						30.0"	10 psi	35 ft
						775 mm	0.7 bar	10.7 m
						36.0"	10 psi	30 ft
600-2448	22.5"-48.0"	21.5"	90.0"	145.0 lbs	25 psi	24.0"	15 psi	40 ft
	575 mm-1250 mm	546 mm	2286 mm	65.7 kg	1.7 bar	600 mm	1.0 bar	12.2 m
						30.0"	15 psi	35 ft
						775 mm	1.0 bar	10.7 m
						36.0"	15 psi	35 ft
900 mm						1.0 bar	10.7 m	
650-2448						42.0"	10 psi	30 ft
						1050 mm	0.7 bar	9.1 m
						48.0"	10 psi	25 ft
						1200 mm	0.7 bar	7.6 m
						36.0"	15 psi	35 ft
600-3660	35.0"-60.0"	34.0"	90.0"	235.0 lbs	20 psi	36.0"	15 psi	35 ft
	900 mm-1550 mm	864 mm	2286 mm	106.5 kg	1.4 bar	900 mm	1.0 bar	10.7 m
650-3660						42.0"	15 psi	35 ft
						1050 mm	1.0 bar	10.7 m
						48.0"	13 psi	30 ft
						1200 mm	0.9 bar	9.1 m
						54.0"	10 psi	25 ft
						1350 mm	0.7 bar	7.6 m
						60.0"	8 psi	20 ft
1500 mm	0.6 bar	6.1 m						
600-4278	41.0"-78.0"	40.0"	102.0"	300.0 lbs	15 psi	42.0"	6 psi	14 ft
	1050 mm-2000 mm	1016 mm	2591 mm	135.9 kg	1.0 bar	1050 mm	0.4 bar	4.3 m
650-4278						54.0"	6 psi	14 ft
						1350 mm	0.4 bar	4.3 m
						66.0"	6 psi	14 ft
						1700 mm	0.4 bar	4.3 m
						78.0"	6 psi	14 ft
						2000 mm	0.4 bar	4.3 m
600-4872	47.0"-72.0"	46.0"	90.0"	325.0 lbs	20 psi	48.0"	15 psi	35 ft
	1200 mm-1850 mm	1168 mm	2286 mm	147.2 kg	1.4 bar	1200 mm	1.0 bar	10.7 m
650-4872						54.0"	13 psi	30 ft
						1350 mm	0.9 bar	9.1 m
						60.0"	10 psi	25 ft
						1500 mm	0.7 bar	7.6 m
						66.0"	8 psi	20 ft
						1700 mm	0.6 bar	6.1 m
						72.0"	8 psi	18 ft
1800 mm	0.6 bar	5.5 m						
600-6096	59.0"-96.0"	58.0"	110.0"	550.0 lbs	12 psi	60.0"	6 psi	14 ft
	1500 mm-2450 mm	1473 mm	2794 mm	249.2 kg	0.8 bar	1500 mm	0.4 bar	4.3 m
650-6096						72.0"	6 psi	14 ft
						1850 mm	0.4 bar	4.3 m
						84.0"	6 psi	14 ft
						2150 mm	0.4 bar	4.3 m
						96.0"	6 psi	14 ft
2450 mm	0.4 bar	4.3 m						

675 Series: Multi-Size Leak Locators with Large Bypass

PART #	SIZE RANGE	DIAMETER	LENGTH	WEIGHT	REQUIRED INFLATION PRESSURE	BYPASS SIZE	PIPE SIZE	MAX ALLOWABLE BACK PRESSURE	
								AIR	WATER
675-2448-4	22.5"-48.0"	21.5"	90.0"	175.0 lbs	20 psi	4.0"	24.0"	15 psi	35 ft
	575 mm-1250 mm	546 mm	2286 mm	79.3 kg	1.4 bar	102 mm	600 mm	1.0 bar	10.7 m
675-2448-6						6.0"	30.0"	15 psi	35 ft
						152 mm	775 mm	1.0 bar	10.7 m
Available with 4" or 6" Bypass							36.0"	15 psi	35 ft
							900 mm	1.0 bar	10.7 m
							42.0"	10 psi	30 ft
							1050 mm	0.7 bar	9.1 m
							48.0"	10 psi	25 ft
							1200 mm	0.7 bar	7.6 m

Pipe Plugs & Accessories